



Main unit

Features:

- Gentle 3D motion and sturdy construction for high capacity
- Wide range of accessory platforms makes it possible to use almost all shapes and sizes of vessels
- LCD display for speed and timer adjustment. Speed and timer can be viewed simultaneously
- Electronic adjustment of speed and built-in timer
- Timing and continuous operation mode

Main Data Description	
Voltage [VAC]	100~240
Frequency [Hz]	50/60
Power [W]	50
Shaking Movement	3D orbital
Orbital Angle [°]	±7/±9
Max. Shaking Weight [kg]	5
Speed Range [rpm]	10 – 70
Speed Display	LCD
Timer	Yes
Timer Display	LCD
Time Setting Range [min]	1 – 1199
Run Type	Time / Continuous Operation
Table Oscillation Braking Device	Yes
Overall Dimensions [D×W×H mm]	430×360×106
Weight [kg]	9
Permissible Ambient Temperature [°C]	5–40
Permissible Relative Humidity	80%
Protection Class acc. To DIN EN60529	IP21

Ordering Information

Cat No.	Descriptions
834210010000	SK-D3307-Pro , LCD Digital 3D Shaker, angle 7°,110V-220V/50HZ/60HZ,US plug
834210110000	SK-D3307-Pro , LCD Digital 3D Shaker, angle 7°,110V-220V/50HZ/60HZ,Cn plug
834210210000	SK-D3307-Pro , LCD Digital 3D Shaker, angle 7°,110V-220V/50HZ/60HZ, Euro plug
834210310000	SK-D3307-Pro , LCD Digital 3D Shaker, angle 7°,110V-220V/50HZ/60HZ,UK plug
834220010000	SK-D3307-Pro , LCD Digital 3D Shaker, angle 7°,110V-220V/50HZ/60HZ,US plug
834220110000	SK-D3307-Pro , LCD Digital 3D Shaker, angle 7°,110V-220V/50HZ/60HZ,Cn plug
834220210000	SK-D3307-Pro , LCD Digital 3D Shaker, angle 7°,110V-220V/50HZ/60HZ, Euro plug
834220310000	SK-D3307-Pro , LCD Digital 3D Shaker, angle 7°,110V-220V/50HZ/60HZ,UK plug