DM0424 & DM0408 series

DLAB low speed clinical centrifuges are widely used in the medical industry. Ideal for separation of serum, plasma, urine, faecal samples in biochemical & medical laboratories. It is an essential equipment of every clinical laboratory, blood bank, medical college and medical research institute.z

DM0424

Clinical Centrifuge

Features:

• Max. speed 4000rpm.

Noise

- Rotor speed can be set in RPM/RCF, with 3 programs storage capacity for routine applications.
- Max. capacity 50ml×4, Adapt to different sizes of blood collection tubes and centrifuge tubes suitable for swing out rotor and angle rotor.
- Automatic internal diagnosis and self-detection.
- Maintenance-free brushless DC motor.





≤60dB(A)

Specifications	DM0424	DM0408
Speed range	500-4000rpm increment: 100rpm	300-4000rpm increment: 100rpm
Max. RCF	2500×g	1900×g
Speed accuracy	±100rpm	±100rpm
Rotor	Swing6×15ml Swing4×50ml Angle 24×15 ml, Angle 12×10ml/8×15ml	Angel 8×15ml(Default), Angel 10ml×12
Run time	1-99min, HOLD	1-99min, HOLD
Motor	Brushless DC motor	Brushless DC motor
Display	LCD	LED
Program	Blood: 3200rpm,10min. Urine: 1800rpm,5min. Faecal: 1300rpm,10min.	Blood: 3200rpm, 10min Urine: 1800rpm,5min Faecal: 1300rpm, 10min
Safety Device	Automatic internal diagnosis	Automatic internal diagnosis
Acceleration/deceleration	3 ↑ 4 ↓ steps	25s ↑ 35s ↓
Power	Single phase, 100V-240V, 50Hz/60Hz	Single phase, 100V-240V, 50Hz/60Hz
Dimension(W \times D \times H)	364×440×268mm	286×367×227mm
Weight	14.5kg	9.2kg

≤62dB(A)



DM0408Clinical Centrifuge

Features:

- Speed range of 300-4000rpm.
- 3 programs storage capacity for routine applications.
- Automatic internal diagnosis.
- Maintenance free brushless DC motor .



DM0424 & DM0408 series | Rotors and Adapters

Available rotors



Cat. No.19400082 **S6-15** for DM0424

Max. speed: 4000rpm Rotor capacity: 15ml×6 Rotor material: Aluminum alloy Default adaptor: A15P22, A5P17

Available adapters



A15P30

Cat. No.19500024

50ml change 15ml adapter, Adapted to 17×120mm centrifuge tube, $13/16 \times 100$ mm blood collection tube 4pcs/pk, for S4-50



Cat. No.19400100 **S4-50**

for DM0424

Max. Speed: 4000rpm Rotor capacity: 50ml×4 Rotor material: Aluminum alloy Default adaptor: A15P30, A5P17



A24-15P Cat. No.19400101

for DM0424

Max. speed: 4000rpm Rotor capacity: 15ml×24

Rotor material: High strength plastic Default adaptor: A15P22, A5P17



A15P22

Cat. No.19500021

15ml adapter, Adapted to 17×120mm centrifuge tube, $13/16 \times 100$ mm blood collection tube 24 pcs/pk,

for S6-15, A24-15P, A8-15P



A8-15P

Cat. No.19400084

for DM0424/DM0408

Max. Speed: 4000rpm Rotor capacity: $15ml \times 8$

Rotor material: High strength plastic

Default adaptor: A15P22



A5P17

Cat. No.19500022

5ml adapter, Adapted to 13×75 mm blood collection tube 24 pcs/pk, for S4-50, S6-15, A24-15P



A12-10P Cat. No.19200348

for DM0424/DM0408 DM0412/DM0412S

Cat.No. 19200348

Rotor capacity: $15ml \times 8,10ml \times 12$ Rotor material: High strength plastic



A2P17

Cat. No.19500023

(Optional)

1.5/2ml Cryogenic Vials/ centrifuge tube adapter, 24 pcs/pk, for S4-50, S6-15, A24-15P, A12-10P, A6-50P