

# MW-12A

## Technical Specifications

Wash programs	up to 100
Wash cycles	0 to 9
Dispensing volume	50 up to 3000 $\mu$ l
Bottom collision protection	automatic
Residual volume per well	< 2 $\mu$ l
Soak time	0 to 300 seconds
Shaking time	0 to 300 seconds
Manifold options	1 x 8, 1 x 12
Standard bottle set	2 x 2L (detergent), 1 x 2L (Waste) 1 x 2L (distilled water)
Input	soft keyboard
Power supply	100-240V ~, 50/60Hz
Temperature	5 $^{\circ}$ C ~35 $^{\circ}$ C
Humidity	15~85%
Dimension	400mm (L) x 330mm (W) x 145mm (H)
Weight	7.2Kg



MINDRAY

www.mindray.com



## MW-12A

- Compatible with flat, U- or V-bottom plates
- 2 wash modes with interchangeable manifolds for 8- and 12-well strips
- Automatic bottom detection and collision protection
- Variable Shaking and soak time
- Stores up to 100 user-defined protocols
- Sweep function with aspiration
- On-board automatic self-diagnostic program
- Automatic liquid monitoring system
- Includes aerosol protection cover



**MINDRAY™**

Mindray Building, Keji 12th Road South, High-tech Industrial Park,  
Nanshan, Shenzhen 518057, P. R. China  
Tel: +86 755 26582492, 26582888 Fax: +86 755 26582680  
E-mail: info-market@mindray.com Website: www.mindray.com

DISTRIBUTOR:

